

# Delo<sup>®</sup> Protection for Construction Equipment



## Hydraulic System

Rando<sup>®</sup> HD 68  
Rando<sup>®</sup> HD 100  
Delo<sup>®</sup> Silver SAE 10W  
Delo<sup>®</sup> Silver SAE 30  
Delo<sup>®</sup> Silver SAE 40  
Delo<sup>®</sup> TorqForce SAE 10W  
Delo<sup>®</sup> TorqForce SAE 30

## Transmission

Delo<sup>®</sup> TorqueForce SAE 10W  
Delo<sup>®</sup> TorqueForce SAE 30  
Texamatic 1888  
Delo<sup>®</sup> Silver SAE 10W  
Delo<sup>®</sup> Silver SAE 30  
Delo<sup>®</sup> Silver SAE 40

## Engine Crankcase

Delo<sup>®</sup> 400 Multigrade SAE 15W-40  
Delo<sup>®</sup> Gold Ultra SAE 15W-40  
Delo<sup>®</sup> Silver Multigrade SAE 20W-50  
Delo<sup>®</sup> Silver Monograde SAE 40

## Coolant System

Delo<sup>®</sup> XLC Anti-Freeze/Coolant

## Bearings and Grease Points

Black Pearl Grease EP 2  
Delo<sup>®</sup> Grease ESI 2  
Marfak Multipurpose 2 & 3  
Multifak EP 2  
Delo<sup>®</sup> Heavy Duty Moly 5% EP 2

## Differential and Gear Drives

Delo<sup>®</sup> Gear EP 5 SAE 80W-90  
Delo<sup>®</sup> Gear EP 5 SAE 85W-140  
Delo<sup>®</sup> Gear EP 5 SAE 140  
Delo<sup>®</sup> Torq Force SAE 50

The product recommendations provide general guidelines for use in construction. All manufacturers have different coolant and lubricant requirements and recommendations. It is strongly recommended to consult the Original Equipment Manufacturers (OEM) manual to confirm the appropriate product is used for the application and consistent with the equipment operating conditions and customer's maintenance practices. It is the responsibility of the end user to ensure that products are used in the applications which they are intended for.

© 2016 Chevron Pakistan Lubricants (Private) Limited. All rights reserved. All trademarks are property of Chevron Intellectual Property LLC.

A Chevron company product

# Delo<sup>®</sup>

## Let's go further.™